



(19)

(11) Publication number: **05176306 A**

Generated Document.

**PATENT ABSTRACTS OF JAPAN**(21) Application number: **03341122**(51) Intl. Cl.: **H04N 7/08 H04M 1/27 H04N 5/44 H04N 5/445**(22) Application date: **24.12.91**

(30) Priority:

(43) Date of application  
publication: **13.07.93**(84) Designated contracting  
states:(71) Applicant: **TOSHIBA CORP  
TOSHIBA AVE CORP**(72) Inventor: **MORIKAWA TAKEO  
OMURA HISASHI  
WATABE KEIICHI**

(74) Representative:

**(54) TRANSMITTING  
EQUIPMENT AND  
RECEIVING EQUIPMENT  
FOR TELEVISION SIGNAL**

(57) Abstract:

**PURPOSE:** To obtain an autodialing control device for automatically executing dialing operation of a telephone set by means of a telephone number displayed on a TV program.

**CONSTITUTION:** Telephone information is superposed during the vertical blanking interval of a TV signal and transmitted by/from a broadcasting station side 1. A telephone information extracting part 26 on the receiving side 2 extracts the telephone information, a memory 28 stores the information when it is effective information, and when a viewer turns on a switch 29, a telephone line switching part 31 is connected to an NTT side line 32. At the time of dialing the telephone number stored in the memory 28, a correct and quick calling can be attained.

COPYRIGHT: (C)1993,JPO&Japio

